

REFRIGERANT R422A

Page: 1

Compilation date: 28/05/2015

Revision date: 08/03/2018

Revision No: 1a

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: REFRIGERANT R422A

Product code: R422A

Synonyms: FREON MO79

ISCEON MO79

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: National Refrigerants Ltd

4 Watling Close

Sketchley Meadows Business Park

Hinckley

Leicestershire

LE10 3EZ

United Kingdom

- Tel: 01455 630790
- Fax: 01455 630791

Email: sds@nationalref.com

1.4. Emergency telephone number

Emergency tel: Carechem24 +44 (0)1865 407333

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Press. Gas: H280

Most important adverse effects: Contains gas under pressure; may explode if heated.

2.2. Label elements

Label elements:

Hazard statements: H280: Contains gas under pressure; may explode if heated.

Hazard pictograms: GHS04: Gas cylinder



Signal words: Warning

Precautionary statements: P410+403: Protect from sunlight. Store in a well-ventilated place.

REFRIGERANT R422A

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

| PENTAFLUOROETHANE - | REACH registered number | or/s). 01-2110/85636-25 |
|---------------------|--------------------------|-------------------------|
| FENTAFLUURUEITIANE | REACT TEGISLETED THUT DE | er(s). 01-2119400000-20 |

workplace exposure limit.

| EINECS | CAS | PBT / WEL | CLP Classification | Percent | |
|------------|-----------------|--|-------------------------------------|---------|--|
| 206-557-8 | 354-33-6 | Substance with a Community workplace exposure limit. | Press. Gas: H280 | 85.100% | |
| REFRIGERAN | IT R134A - REAC | H registered number(s): 01-2119459 | 374-33 | | |
| 212-377-0 | 811-97-2 | Substance with a Community workplace exposure limit. | Press. Gas: H280 | 11.500% | |
| ISOBUTANE | | | | | |
| 200-857-2 | 75-28-5 | Substance with a Community | Flam. Gas 1: H220; Press. Gas: H280 | 3.400% | |

Section 4: First aid measures

| 4.1. Description of first aid measures |
|---|
| |
| Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the |

| Skin contact: | Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the |
|------------------------------|---|
| | affected skin with running water for 10 minutes or longer if substance is still on skin. Do not |
| | use hot water. If frostbite has occurred call a physician. |
| Eye contact: | Bathe the eye with running water for 15 minutes. Consult a doctor. |
| Ingestion: | Injestion is unlikely because of the physical properties and is not expected to be hazardous. |
| | As this product is a gas refer to inhalation section. |
| Inhalation: | Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, |
| | check for breathing and apply artificial respiration if necessary. Consult a doctor. |
| 4.2. Most important symptom | ns and effects, both acute and delayed |
| Skin contact: | There may be redness or whiteness of the skin in the area of exposure. Frost-bite may occur |
| | causing the affected area to become white and numb. |
| Eye contact: | There may be severe pain. Corneal burns may occur. May cause permanent damage. |
| Ingestion: | It is unlikely that this substance will be swallowed due to its physical properties. |
| Inhalation: | Inhalation may produce the following symptoms: Shortness of breath, dizziness, weakness, |
| | nausea, headache, narcosis, irregular cardiac activity. Asphyxia. May cause cardiac |
| | arrhythmia. |
| | |
| Delayed / immediate effects: | May cause cardiac arrhythmia. |

REFRIGERANT R422A

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: The product is not flammable. Suitable extinguishing media for the surrounding fire should be used. Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Non flamable gas.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point.

6.2. Environmental precautions

Environmental precautions: Stop release if safe to do so. Prevent from entering sewers, basements and work pits, or any place where the accumulation can be dangerous.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Material evaporates. Ventilate the area, especially low or enclosed places where heavy vapours might collect.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Store at a temperature not exceeding 45°C.

Suitable packaging: Must only be kept in original packaging.

REFRIGERANT R422A

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PENTAFLUOROETHANE

| orkplace ex | cposure limits: | Re | spirable dust | |
|-------------|-----------------|--------------|---------------|--------------|
| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
| EU | 1000 ppm | - | - | |
| EFRIGERAN | NT R134A | | | |
| EU | 4240 mg/m3 | - | - | |
| OBUTANE | | | | |
| | 2400 mg/m3 | 9600 mg/m3 | | |

Hazardous ingredients:

PENTAFLUOROETHANE

| Туре | Exposure | Value | Population | Effect |
|------|-----------------------|-------------|------------|----------|
| DNEL | Inhalation | 16444 mg/m3 | Workers | Systemic |
| DNEL | Inhalation | 1753 mg/m3 | Consumers | Systemic |
| PNEC | Fresh water | 0.1 mg/l | - | - |
| PNEC | Fresh water sediments | 0.6 mg/kg | - | - |

REFRIGERANT R134A

| Туре | Exposure | Value | Population | Effect |
|------|------------------------------------|-------------|------------|----------|
| DNEL | Inhalation | 2476 mg/m3 | Workers | Systemic |
| DNEL | Inhalation | 2476 mg/m3 | Consumers | Systemic |
| PNEC | Fresh water | 0.01 mg/l | - | - |
| PNEC | Marine water | 0.75 mg/l | - | - |
| PNEC | Microorganisms in sewage treatment | 73 mg/l | - | - |
| DNEL | Inhalation | 13936 mg/m3 | Workers | Systemic |
| PNEC | Fresh water sediments | 0.75 mg/kg | - | - |

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection:Self-contained breathing apparatus must be available in case of emergency. Vapours are
heavier than air and can cause suffocation by reducing the oxygen available for breathing.Hand protection:Protective gloves. Material: Low temperature resistant gloves. The suitability for a specific
workplace should be discussed with the producers of the protective gloves.

REFRIGERANT R422A

Eye protection: Safety glasses with side-shields. Safety goggles. Face-shield. Safety glasses.

Skin protection: Protective clothing.

Environmental: Gas escapes to be kept to the minimum by engineering processes and operating methods.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| State: | Liquified gas |
|-------------------------------|--------------------------|
| Colour: | Colourless |
| Odour: | Barely perceptible odour |
| Boiling point/range°C: | -46.2 to -41.5 |
| Flammability limits %: lower: | Not applicable. |
| Flash point°C: | Not applicable. |
| Relative density: | Vapour: 3.9 (Air=1) |

Melting point/range°C: No data available. upper: Not applicable. Vapour pressure: 10.9 Bar at 200C

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

REFRIGERANT R422A

Page: 6

Hazardous ingredients:

PENTAFLUOROETHANE

| GASES | RAT | 4H LC50 | 800000 | ppmV |
|-----------------------------|--|----------------------------------|------------------------|---------------------------|
| REFRIGERANT R134A | | | | |
| GASES | RAT | 4H LC50 | 567000 | ppmV |
| ONOLO | | 411 2000 | 307000 | |
| Toxicity values: | No data available. | | | |
| Symptoms / routes of exposu | ire | | | |
| Skin contact: | There may be red | ness or whiteness of the skin | in the area of expos | ure. Frost-bite may occur |
| | | ed area to become white and | • | |
| Eve contact: | There may be severe pain. Corneal burns may occur. May cause permanent damage. | | | |
| - | It is unlikely that this substance will be swallowed due to its physical properties. | | | |
| - | Inhalation may produce the following symptoms: Shortness of breath, dizziness, weakness, | | | |
| innalation. | 21 | 0 7 1 | | |
| | nausea, headache | e, narcosis, irregular cardiac a | activity. Asphyxia. Ma | ay cause cardiac |
| | arrhythmia. | | | |
| elayed / immediate effects: | May cause cardiad | c arrhythmia. | | |
| tion 12: Ecological inforn | nation | | | |

12.1. Toxicity

Hazardous ingredients:

REFRIGERANT R134A

| Daphnia magna | 48H EC50 | 980 | mg/l |
|--|-----------|-----|------|
| GREEN ALGA (Selenastrum capricornutum) | 72H ErC50 | 118 | mg/l |
| RAINBOW TROUT (Oncorhynchus mykiss) | 96H LC50 | 450 | mg/l |

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Ozone Depletion Potential (ODP): 0 (R11 = 1) R422A Global Warming Potential (GWP): 3143

(CO2=1) Contains fluoronated greenhouse gases covered by the Kyoto Protocol.

REFRIGERANT R422A

Section 13: Disposal considerations

| 13.1. Waste treatment methods | | |
|-------------------------------|---|--|
| Disposal operations: | Product evaporates. Recover to a recovery cylinder and return to a refrigerant recovery | |
| | facility. | |
| Recovery operations: | Consult manufacturer or supplier for information regarding recovery and recycling of the | |
| | product. If recovery is not possible, incinerate at a licenced instalation. | |
| Waste code number: | 14 06 01 | |
| Disposal of packaging: | Return to supplier. | |
| NB: | The user's attention is drawn to the possible existence of regional or national regulations | |
| | regarding disposal. | |
| Action 14: Transport inform | nation | |

Section 14: Transport information

14.1. UN number

UN number: UN3163

14.2. UN proper shipping name

Shipping name: LIQUEFIED GAS, N.O.S.

(PENTAFLUOROETHANE;

REFRIGERANT R134A)

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: C/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Contains fluorinated greenhouse gases covered by the Kyoto Protocol.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

REFRIGERANT R422A

Page: 8

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.