

REFRIGERANT R455A

Page: 1

Compilation date: 16/02/2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: REFRIGERANT R455A

Product code: R455A

Synonyms: SOLSTICE L40X

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Refrigerant

1.3. Details of the supplier of the safety data sheet

Company name: National Refrigerants Ltd

4 Watling Close

Sketchley Meadows Business Park

Hinckley

Leicestershire

LE10 3EZ

United Kingdom

Tel: 01455 630790

Fax: 01455 630791

Email: sds@nationalref.com

1.4. Emergency telephone number

Emergency tel: Carechem24 +44 (0)1865 407333

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Gas 1: H220; Press. Gas: H280

Most important adverse effects: Extremely flammable gas. Contains gas under pressure; may explode if heated.

2.2. Label elements

Label elements:

Hazard statements: H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

Hazard pictograms: GHS02: Flame



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

REFRIGERANT R455A

Page: 2

No smoking.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: [In case of inadequate ventilation] wear respiratory protection.

P308+313: IF exposed or concerned: Get medical advice/attention.

P410+403: Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN - REACH registered number(s): 01-0000019665-61

EINECS	CAS	PBT / WEL	CLP Classification	Percent		
-	754-12-1	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	75.500%		
DIFLUODOMETHANIE						

DIFLUOROMETHANE

200-839-4	75-10-5	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	21.500%
		workplace exposure limit.		

Non-classified ingredients:

REFRIGERANT R744

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-696-9	124-38-9	-	Press. Gas: H280; -: EUH044	3.000%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin. Do not

use hot water. If frostbite has occurred call a physician.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Not applicable.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious,

check for breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be redness or whiteness of the skin in the area of exposure. Frost-bite may occur

causing the affected area to become white and numb.

REFRIGERANT R455A

Page: 3

Eye contact: There may be pain and redness. Corneal burns may occur. May cause permanent damage.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Suitable

extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If

outside keep bystanders upwind and away from danger point.

6.2. Environmental precautions

Environmental precautions: Stop release if safe to do so. Prevent from entering sewers, basements and work pits, or any

place where the accumulation can be dangerous.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Material

evaporates. Ventilate the area, especialy low or enclosed places where heavy vapours might

collect.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the

area. Avoid the formation or spread of mists in the air.

REFRIGERANT R455A

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources

of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting

and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL		
EU	500 ppm	-	-	-		
DIELLODOMETHANE						

DIFLUOROMETHANE

UK	1000 ppm	-	-	-
----	----------	---	---	---

DNEL/PNEC Values

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	273 mg/m3	Workers	-
PNEC	Fresh water	> 0.1 mg/l	-	-
PNEC	Marine water	> 0.01 mg/l	-	
PNEC	Fresh water sediments	> 1.77 mg/kg	-	-
PNEC	Soil (agricultural)	> 1.54 mg/kg	-	-

DIFLUOROMETHANE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (developmental tox)	16444 mg/m3	Workers	Systemic
DNEL	Inhalation (developmental tox)	1753 mg/m3	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are

not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

REFRIGERANT R455A

Page: 5

Eye protection: Safety glasses with side-shields. Safety goggles. Face-shield. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquified gas
Colour: Colourless

Odour: Characteristic odour

Flammability limits %: lower: 11.8% at 23oC upper: 12.9% at 23oC

Flash point°C: Not applicable.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN

GASES	RAT	4H I C50	> 400000	Vmqq
GASES	KAI	4H LC50	> 400000	ppiliv

REFRIGERANT R455A

Page: 6

DIFLUOROMETHANE

GASES	RAT	LD50	520000	Vmqq
OAOLO	11/7/1	LD30	320000	ppiiiv

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be redness or whiteness of the skin in the area of exposure. Frost-bite may occur

causing the affected area to become white and numb.

Eye contact: There may be pain and redness. Corneal burns may occur. May cause permanent damage.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN

ALGAE	96H LC50	> 100	mg/l
Daphnia magna	48H EC50	> 83	mg/l
FISH	96H ErC50	>197	mg/l

DIFLUOROMETHANE

ALGAE	96H ErC50	142	mg/l
Daphnia magna	48H EC50	652	mg/l
FISH	96H LC50	1.057	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

REFRIGERANT R455A

Page: 7

13.1. Waste treatment methods

Disposal operations: Product evaporates.

Recovery operations: Consult manufacturer or supplier for information regarding recovery and recycling of the

product. If recovery is not possible, incinerate at a licenced instalation.

Disposal of packaging: Return to supplier.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3161

14.2. UN proper shipping name

Shipping name: LIQUEFIED GAS, FLAMMABLE, N.O.S.

(2,3,3,3-TETRAFLUOROPROP-1-EN; DIFLUOROMETHANE)

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: B/D **Transport category:** 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH044: Risk of explosion if heated under confinement.

REFRIGERANT R455A

Page: 8

H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

Legal disclaimer: National Refrigerants Ltd believes that the information and recommendations contained herein (including data and statments) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated. National Refrigerants expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.