

REFRIGERANT R454A

Page: 1

Compilation date: 20/03/2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: REFRIGERANT R454A

Product code: R454A

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: National Refrigerants Ltd

4 Watling Close

Sketchley Meadows Business Park

Hinckley

- Leicestershire
- LE10 3EZ

United Kingdom

- Tel: 01455 630790
- Fax: 01455 630791

Email: sds@nationalref.com

1.4. Emergency telephone number

Emergency tel: Carechem24 +44 (0)1865 407333

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Press. Gas: H280; Flam. Gas 1: H220

Most important adverse effects: Extremely flammable gas. Contains gas under pressure; may explode if heated.

2.2. Label elements

Label elements:

Hazard statements: H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

Hazard pictograms: GHS02: Flame

GHS04: Gas cylinder



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

REFRIGERANT R454A

Page: 2

P381: In case of leakage, eliminate all ignition sources.

P410+P403: Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN - REACH registered number(s): 01-0000019665-61

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
468-710-7	754-12-1	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	50-70%	
DEEDIGEDANIT D22 DEACH registered number(c): 01 2110471212 47					

REFRIGERANT R32 - REACH registered number(s): 01-2119471312-47

200-839-4	75-10-5	Substance with a Community	Flam. Gas 1: H220; Press. Gas:	30-50%
		workplace exposure limit.	H280; -: EUH044	

Section 4: First aid measures

4.1. Description of first aid m	easures		
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.		
	Drench the affected skin with running water for 10 minutes or longer if substance is still		
	on skin. Do not use hot water. If frostbite has occurred call a physician.		
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
Ingestion:	Not applicable.		
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If		
	unconscious, check for breathing and apply artificial respiration if necessary. Consult a		
	doctor.		
4.2. Most important symptom	ns and effects, both acute and delayed		
Skin contact:	There may be redness or whiteness of the skin in the area of exposure. Frost-bite may		
	occur causing the affected area to become white and numb.		
Eye contact:	There may be pain and redness. Corneal burns may occur. May cause permanent		
	damage.		
Ingestion:	There may be irritation of the throat.		
Inhalation:	No symptoms.		
4.3. Indication of any immediate medical attention and special treatment needed			

Immediate / special treatment: Not applicable.

REFRIGERANT R454A

Section 5: Fire-fighting meas	sures
5.1. Extinguishing media	
Extinguishing media:	Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
5.2. Special hazards arising f	rom the substance or mixture
Exposure hazards:	Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.
5.3. Advice for fire-fighters	
Advice for fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.
Section 6: Accidental release	emeasures
6.1. Personal precautions, pr	otective equipment and emergency procedures
Personal precautions:	Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. If outside keep bystanders upwind and away from danger point.
6.2. Environmental precautio	ns
Environmental precautions:	Stop release if safe to do so. Prevent from entering sewers, basements and work pits, or any place where the accumulation can be dangerous.
6.3. Methods and material for	containment and cleaning up
Clean-up procedures:	Do not use equipment in clean-up procedure which may produce sparks. Material evaporates. Ventilate the area, especialy low or enclosed places where heavy vapours might collect.
6.4. Reference to other section	ons
Reference to other sections:	Refer to section 8 of SDS.
Section 7: Handling and stor	age
7.1. Precautions for safe han	dling
Handling requirements:	Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.
7.2. Conditions for safe stora	ge, including any incompatibilities
Storage conditions:	Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area.
Suitable packaging:	Ensure lighting and electrical equipment are not a source of ignition. Must only be kept in original packaging.

REFRIGERANT R454A

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN

Workplace exposure limits:			Respirable dust		
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL	
EU	500 ppm	-	-	-	
REFRIGERANT R32					
UK	1000 ppm	-	-	-	

DNEL/PNEC Values

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	273 mg/m3	Workers	-
PNEC	Fresh water	> 0.1 mg/l	-	-
PNEC	Marine water	> 0.01 mg/l	-	-
PNEC	Fresh water sediments	> 1.77 mg/kg	-	-
PNEC	Soil (agricultural)	> 1.54 mg/kg	-	-

REFRIGERANT R32

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (developmental tox)	13936 mg/m3	Workers	Systemic
DNEL	Inhalation (developmental tox)	2476 mg/m3	Consumers	Systemic
PNEC	Fresh water	0.142 mg/l	-	-
PNEC	Fresh water sediments	0.534 mg/kg	-	-

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical
	equipment are not a source of ignition.
Respiratory protection:	Respiratory protection not required.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses with side-shields. Safety goggles. Face-shield. Ensure eye bath is to
	hand.
Skin protection:	Protective clothing.

REFRIGERANT R454A

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquified gas

Colour: Colourless

Odour: Characteristic odour

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN

GASES RAT 4H LC50 > 400000 ppmV	
---------------------------------	--

REFRIGERANT R32

GASES RAT LD50 520000 ppmV	
----------------------------	--

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be redness or whiteness of the skin in the area of exposure. Frost-bite may

occur causing the affected area to become white and numb.

REFRIGERANT R454A

Eye contact: There may be pain and redness. Corneal burns may occur. May cause permanent

damage.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

2,3,3,3-TETRAFLUOROPROP-1-EN

ALGAE	96H LC50	> 100	mg/l
Daphnia magna	48H EC50	> 83	mg/l
FISH	96H ErC50	>197	mg/l

REFRIGERANT R32

ALGAE	96H ErC50	142	mg/l
Daphnia magna	48H EC50	652	mg/l
FISH	96H LC50	1.057	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods	
Disposal operations:	Product evaporates.
-	
Recovery operations:	Consult manufacturer or supplier for information regarding recovery and recycling of the
	product. If recovery is not possible, incinerat at a licensed installation.
Disposal of packaging:	Return to supplier.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.
	regulations regarding disposal.

REFRIGERANT R454A

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN3161

14.2. UN proper shipping name

Shipping name: LIQUEFIED GAS, FLAMMABLE, N.O.S.

(DIFLUOROMETHANE; 2,3,3,3-TETRAFLUOROPROP-1-EN)

Marine pollutant: No

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: B/D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH044: Risk of explosion if heated under confinement.
	H220: Extremely flammable gas.
	H280: Contains gas under pressure; may explode if heated.
Legal disclaimer:	National Refrigerants Ltd believes that the information and recommendations contained
	herein (including data and statments) are accurate as of the date hereof. NO
	WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF
	MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE
	CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided

REFRIGERANT R454A

Page: 8

herein relates only to the specific product designated. National Refrigerants expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.